











**FOOD & PRODUCE** 



TECHNICAL PRODUCTS

## Intuitive Multi-Use Temperature Logger for reliable low-cost cold chain monitoring.

**temp**mate.®-M1 our best data loggers for temperature recording with internal or external temperature sensor, multifunction display and automatic PDF report generation.















USB IP 67 Temperature range connection protected -30°C to +70°C

EN 12830 Compliant

Automatic PDF report co

GDP compliant

# mec Messtechnik GmbH · V1.8-02/2019-EN · Technical Changes and Errors excepted

### tempmate.®-M1

#### If temperature matters.





#### Easy Handling





after software setup



O2 Attach started tempmate.® to your shipment



03 Connect stopped logger directly to USB port



04 Automated PDF report with all important details

#### Curious about your cold chain? tempmate. 9-M1 continuously monitors all relevant data.

tempmate. •-M1 loggers are specially designed for temperature monitoring in pharmaceutical cold chain logistics. As preprogrammed device **temp**mate.®-M1 can be instantly used to control your temperature sensitive consignment. The PDF report created contains detailed information such as data curve, every single measurement as a table and statistical information. With the optional free available **temp**base.® software, you can ensure individual logger configuration and detailed data analysis or data management is also possible. Moreover, the device does not require labeling per IATA's Dangerous Goods Regulations.

#### Your Benefits at a Glance

- Product-related temperature monitoring along the entire cold chain, in warehouses or fridges
- Cost-effective and reliable
- Smart design, intuitive operation
- Waterproof and food compatible
- Free available software for individual logger configuration
- Detailed PDF report including graph and table
- Multifunction display with battery indicator

Technical Specifications		Interval	10sec. up to 11h 59min. (default 15 min.)
		Alarm Settings	adjustable up to 5 alarm limits
Temperature Sensor	NTC internal and external optional	Alarm Type	Single alarm or cumulative
Measuring Range	$-30^{\circ}$ C to $+70^{\circ}$ C ( $-40^{\circ}$ C to $+90^{\circ}$ C with ext. Sensor)	Battery	CR2032 / replaceable by customer
Accuracy	$\pm 0.5^{\circ}$ C (at -20 $^{\circ}$ C to + 40 $^{\circ}$ C)	Dimensions	80mm x 34mm x 14mm (L x W x D)
T90	5min ( internal sensor ) / 30s ( external sensor )	Protection Class	IP67
Resolution	0.1 °C	System Requirements	PDF Reader
Data Storage	32,000 values	Connection Interface	USB 2.0, A-Type
Display	Multifunction LCD	Certification	12830, validation certificate, CE, RoHS
Start Setting	Manually by pressing button or automatically programmed start time	Software	tempbase.® -D / free download
Recording Time	By customer programmable / up to 12 months	Interface to PC	integrated USB port
		Automatic PDF Reporting	yes

